

## GenPole Flagpole

NOTE: A generator should not be run in or in close proximity to a living area. Allow components to cool after running generator before touching.

IMPORTANT: We highly recommend keeping the first couple feet of a silicone tubing run fairly straight to reduce heat buildup and extend the life of the tubing. A tight bend will cause a kink and premature failure.

### **Installation:**

1. Place flagpole into holder that is already secured.
2. Attach top flag to the top clips, attach bottom flag to the remaining clips.
3. Slide top section apart and use arrow on the top section to orient the stainless button to the hole. Repeat each section until at full height.
4. Slide polycarbonate locking ring over the bottom button of the flagpole. This helps to ensure exhaust is transmitted out of the top of the GenPole.
5. Remove plug on generator attachment port.
6. Attach exhaust components to the generator attachment port.
7. Start generator, enjoy!

### **Removal (while pole is still secured in a base):**

1. Once cooled, lower one section at a time by pushing stainless buttons and slide pole sections together. This can be done with the pole in the vertical position.
2. Remove flags.
3. Reinsert plug into generator attachment port (this is intended to prevent insects from inhabiting the tube when used without generator).
4. Wipe off any exhaust condensation from the inside of the base. It is normal for water to be present at the base during operation.

Positive feedback is greatly appreciated, but if you are not satisfied, please contact us.

See us at: <https://genexhaust.com/>